# **MAGLOCKS**



# UL Listed Electromagnetic Locks



Quality
Intelligence
Precision

BEA's Maglocks offer the ultimate protection for most access control applications.

- Lock status sensor (bond sensor) and visual LED on 600 and 1200 lb models
- Includes adjustable relock time delay (0 90 secs)
- Field selectable 12/24 VDC
- Installation hardware included for typical applications
- Convenient plug-in wire terminals
- Available for single doors and double doors without center mullion

WWW.BEASENSORS.COM





# MAGLOCK TECHNICAL SPECS

10MAGLOCK3UL Single 10MAGLOCK6UL Double



**HOLDING FORCE** 600 lbs

**INPUT VOLTAGE** 12 or 24 VDC

Power Supply

Single 0.50A @ 12VDC Note: This product is recommended to be

0.25A @ 24VDC Dual used with a UL-Listed

1.00A @ 12VDC 0.50A @ 24VDC

**CURRENT DRAW** 

Single

0.50A @ 12VDC

0.25A @ 24VDC

Dual

1.03A @ 12VDC

0.52A @ 24VDC

**CURRENT DRAW** 

(250mm x 47mm x 26mm) Dual

19.76" x 1.85" x 1.02" (502mm x 47mm x 26mm)

DIMENSIONS

Single

9.84" x 1.85" x 1.02"

**DIMENSIONS** Single

10.47" x 2.91" x 1.58" (266mm x 74mm x 40mm)

Dual 20.94" x 2.91" x 1.58" (532mm x 74mm x 40mm)

10MAGLOCK1UL Single 10MAGLOCK5UL Double



**HOLDING FORCE** 1200 lbs

INPUT VOLTAGE 12 or 24 VDC

> Note: This product is recommended to be used with a UL-Listed

Power Supply



10MAGLOCK1UL 1200LB - SINGLE



MAGLOCK FAMILY OF PRODUCTS

10MAGLOCK3UL 600LB - SINGLE



10MAGLOCK5UL 1200LB - DOUBLE



10MAGLOCK6UL 600LB - DOUBLE



10LZBRMAG1UL (1) 'L' and (1) 'Z'



**HOLD TIMER** 

0-90 sec

**HOLD TIMER** 

0-90 sec

10LZBRMAG3UL (1) 'L' and (1) 'Z' use with 10MAGLOCK3UL



MAG5LZUL MAG6LZUL (2) 'L' and (2) 'Z'



10FILLER12UL 10FILLER34UL FILLER BAR



10UBRACKETUL U-Bracket - Glass Doors



**Vertical Spacer Bars** 



**Armature Housing** 

## MAGLOCK APPLICATIONS



 Install BEA Maglocks in security applications including: portals in hotels, retail outlets or where egress control is needed

Maglocks

**Armature Plate** 

▶ BEA Maglocks, when combined with BEA's other security products, are designed to ensure ultimate security in clean room, airlock, and also mantrap applications

 Clean Room / Airlock Application

## RELATED PRODUCTS

Swinging Door Application



Fly Kits PIR detector for Request to Exit applications Includes: Sensor, Ceiling, and Surface Adapters



Power Supply 12 or 24 VDC with a battery backup option available



Access Control push solution for any indoor application



hograna matile 2 Relay bgic module with 12 nate functions



Touchless Push Plate utilizing microwave motion technology